

MX322 PCB Spring Type Terminal Blcoks, 2.54mm pitches
MX322-254

MX322 PCB Spring Type Terminal Block





DIMENSIONS/POSITIONS

		MX322-254
間距	Pitch	2.54mm
位數	Poles	2 ~ 24Poles
尺寸a	Dimension a	2.54mm
長度 A	Length	A= 2.54xP+3.00mm(P≧2)
塑膠本體	Housing Material	PA 66
端蓋	Cover	PA 66
端子	Contact	Brass, Tin Plated
彈片	Spring	Stainless Strip Steel
電線線徑	Wire Size	20 ~ 26AWG
PCB孔徑	PCB Hole Diameter	1.2mm
環境作業溫度	Operating Temperature	-40℃ to +105℃

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE		
額定電流I_N	Nominal Current I_N	6A
額定橫截面	Nominal Cross Section	
最大負載電流	Maximum load current	6A
絕緣材料	Insulating Material	PA
阻燃等級, 符合UL94 Inflammability class acc. to UL94		V0
額定電壓, UL/CUL Nominal voltage, UL/CUL		150V
額定電流, UL/CUL Nominal current, UL/CUL		6A

